

**AS81659/66**

FEDERAL SUPPLY CLASS  
5935


# NOTICE

THIS DOCUMENT HAS BEEN TAKEN DIRECTLY FROM U.S. MILITARY SPECIFICATION MIL-C-81659/66 AND CONTAINS ONLY MINOR EDITORIAL AND FORMAT CHANGES REQUIRED TO BRING IT INTO CONFORMANCE WITH THE PUBLISHING REQUIREMENTS OF SAE TECHNICAL STANDARDS. THE INITIAL RELEASE OF THIS DOCUMENT IS INTENDED TO REPLACE MIL-C-81659/66. ANY PART NUMBERS ESTABLISHED BY THE ORIGINAL SPECIFICATION REMAIN UNCHANGED.

THE ORIGINAL MILITARY SPECIFICATION WAS ADOPTED AS AN SAE STANDARD UNDER THE PROVISIONS OF THE SAE TECHNICAL STANDARDS BOARD (TSB) RULES AND REGULATIONS (TSB 001) PERTAINING TO ACCELERATED ADOPTION OF GOVERNMENT SPECIFICATIONS AND STANDARDS. TSB RULES PROVIDE FOR (A) THE PUBLICATION OF PORTIONS OF UNREVISED GOVERNMENT SPECIFICATIONS AND STANDARDS WITHOUT CONSENSUS VOTING AT THE SAE COMMITTEE LEVEL, AND (B) THE USE OF THE EXISTING GOVERNMENT SPECIFICATION OR STANDARD FORMAT.

UNDER DEPARTMENT OF DEFENSE POLICIES AND PROCEDURES, ANY QUALIFICATION REQUIREMENTS AND ASSOCIATED QUALIFIED PRODUCTS LISTS ARE MANDATORY FOR DOD CONTRACTS. ANY REQUIREMENT RELATING TO QUALIFIED PRODUCTS LISTS (QPL'S) HAS NOT BEEN ADOPTED BY SAE AND IS NOT PART OF THIS TECHNICAL REPORT.

THIRD ANGLE PROJECTION



ISSUED 2004-05

CUSTODIAN: AE-8/AE-8C1

PROCUREMENT SPECIFICATION: MIL-C-81659

**SAE Aerospace**  
An SAE International Group

## AEROSPACE STANDARD

CONNECTORS, ELECTRICAL, RECTANGULAR, RECEPTACLE, CRIMP CONTACTS, (SINGLE INSERT, TYPE IV, CLASS 1, (-65°C TO +125°C), SERIES 2, SHELL DESIGNATOR A)

**AS81659/66**  
SHEET 1 OF 4

Copyright 2004 SAE International



All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)  
Fax: 724-776-0790

Tel: 724-776-4970 (outside USA)  
Email: [custsvc@sae.org](mailto:custsvc@sae.org)

SAE WEB ADDRESS: <http://www.sae.org>

FOR CONNECTOR DRAWING SEE PAGE 2.




RECOMMENDED MATING POSITION

SUGGESTED PANEL CUT-OUT DIMENSIONS

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.006	.15	.118	3.00	.521	13.23	1.367	34.72	1.725	43.82
.040	1.02	.122	3.10	.541	13.74	1.387	35.23	1.765	44.83
.047	1.19	.133	3.38	.570	14.48	1.425	36.20	1.785	45.34
.050	1.27	.187	4.75	.7185	18.25	1.427	36.25	1.985	50.42
.055	1.40	.198	5.03	.720	18.29	1.437	36.50	1.997	50.72
.065	1.65	.281	7.14	1.000	25.40	1.445	36.70	2.015	51.18
.117	2.97	.297	7.54	1.326	33.68	1.447	36.75	2.027	51.49
								2.250	57.15

## NOTES:

1. DIMENSIONS ARE IN INCHES.
2. METRIC EQUIVALENTS (TO THE NEAREST .01 MM) ARE GIVEN FOR GENERAL INFORMATION ONLY AND ARE BASED UPON 1 INCH = 25.4 MM.
3. DIMENSIONS APPLY AFTER PLATING.
4. NORMAL (01) POLARIZATION POSITION SHOWN. FOR ALTERNATE POSITIONS SEE MIL-C-81659.
5. FOR LOCATION OF DATUMS G AND H REFER TO MIL-C-81659, FIGURE 5.
6. THIS CONNECTOR DOES NOT HAVE A WIRE SEALING GROMMET.



## REQUIREMENTS:

INSERT ARRANGEMENTS SHALL BE IN ACCORDANCE WITH MS3157.

CONTACTS SHALL BE IN ACCORDANCE WITH MIL-C-39029/11 OR MIL-C-39029/12 AS APPLICABLE.

INSTALLING AND REMOVAL TOOLS SHALL BE IN ACCORDANCE WITH MS3156 OR MS3447.